


永茂建机
YONGMAO

STL4200
100t



FEM

Luffing

V5.0-05262023

動臂系列

001
002


Luffing STL4200

Luffing STL4200

STL4200
100t

載荷表 Load Chart

R (m)	倍率 Fall	R(C _{max}) m	C _{max} t	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
90	↘	20.00	100.00	100.00	79.20	65.46	55.69	48.40	42.75	38.24	34.56	31.49	28.91	26.69	24.77	23.09	21.61	20.30
	↓	61.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	44.83	39.21	34.34	30.09	26.33	23.00
80	↘	38.00	100.00	100.00	100.00	100.00	100.00	93.32	79.25	68.02	58.85	51.22	44.77	39.25	34.48	30.30	26.33	23.00
	↓	63.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	47.53	41.99	37.19	33.00	29.33	26.00
70	↘	40.00	100.00	100.00	100.00	100.00	100.00	100.00	84.98	73.00	63.21	55.07	48.19	42.30	37.41	33.00	29.33	26.00
	↓	66.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	45.00	40.00	36.00	32.00	28.00
65	↘	41.00	100.00	100.00	100.00	100.00	100.00	100.00	88.85	77.45	68.15	60.40	53.86	48.00	42.30	37.41	33.00	29.33
	↓	65.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	45.00	40.00	36.00	32.00	28.00
55	↘	42.00	100.00	100.00	100.00	100.00	100.00	100.00	91.65	79.99	70.47	62.40	55.00	48.30	42.30	37.41	33.00	29.33
	↓	55.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	45.00	40.00	36.00	32.00	28.00
45	↘	42.00	100.00	100.00	100.00	100.00	100.00	100.00	92.00	80.00	70.00	62.00	55.00	48.30	42.30	37.41	33.00	29.33
	↓	45.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	45.00	40.00	36.00	32.00	28.00
40	↘	42.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	90.00	80.00	70.00	62.00	55.00	48.30	42.30	37.41	33.00
	↓	45.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	50.00	45.00	40.00	36.00	32.00	28.00



	●	■
F2	1080t	1060t
F3	660t	670t
⊗	585t	

	●	■
F1	550t	545t
⊗	921t	

● 工作狀態支反力 In service reaction ■ 非工作狀態支反力 Out of service reaction
⊗ 整機自由高度重量 (不含平衡重及壓重重量) Total weight of free standing crane (excludes counter weight & ballast.)

Luffing STL4200






YONGMAO HOLDINGS LIMITED




YONGMAO HOLDINGS LIMITED

STL4200

100t



內爬框外廓尺寸
Overall dimensions of the internal climbing frame



內爬開口尺寸
Dimensions of the internal climbing opening

塔身節 Mast	臂長 Jib length	A (m)	B (m)	C (m)	D (m)	H0 (m)
H360LX	65	42	29	44	>5	360 >360 *

塔身節 Mast	臂長 Jib length	H1 (m)	A1 (m)	P (t)	R (t)
H360LX	65	60	24	82.5	180
		X (m)	Y (m)	L (m)	W (m)
		4.9	4.1	5.8	5.2

附著道數 Number of tie collars=(H0-A-C)/B+1

超過100m高度，需降低載荷，請與公司聯繫。

Load should be reduced when the height exceeds 100m. Please contact Yongmao for details.

主要性能參數 Specifications

機構 Mechanism		●		●●			電動機 Motor kW
		m/min	t	m/min	t		
	280LFV500B	0—22 0—48 0—96	50.0 20.0 6.0	0—11 0—24 0—48	100.0 40.0 12.0	900m > 900m *	280
	150DFV260BI	15°—85° 3 min					162
	18RFCV	0—0.5 rpm					4x18.5
	RTV	0—15 m/min					16x5.5

電壓 Voltage	kVA
380V (± 10 %) 50Hz	516

* 與製造商聯繫 Contact us, please.

☆ 標準配置 Standard configuration.

本技術參數不受法律約束，技術資訊請詳見相應說明書。
These specifications and data are not legally binding. For any technical information, please refer to corresponding instructions.

動臂系列

STL4200

100t

Luffing STL4200
Luffing STL4200



YONGMAO HOLDINGS LIMITED



YONGMAO HOLDINGS LIMITED